Nomenclature / Plate System Airmaster Products AM 300

AML 300 H T DE RE-CC,WCH,B1

Series:
AML

Type:
300

Model:
H (Horizontal)
V (Vertical)

Version:

1. Character:
T – Inlet Top
C – Inlet Center
B – Inlet Bottom
DI – Ducted Inlet

2. Character
DE – Ducted Extract

3. Character
RE – Rectangular Supply and Exhaust

Options:

BP	Bypass (standard)
CC	Cooling Module
CP	Condensate Pump
EM	Energy Meter
ePM_{10} 70%	Supply air filter ePM_{10} 70%
$ePM_{2,5}$ 65%	Supply air filter $ePM_{2,5}$ 65%
ePM_1 85%	Supply air filter ePM_1 85%
HS	Heating Surface (Virtual Preheat Function and Comfort Heater Function)
SD	Motor-driven Supply Air Damper (standard)
WCH	Water Comfort Heater
CO	CO_2 Sensor
HY	Hygrostat
ICO	Internal CO_2 Sensor
PIR	Motion Sensor
IPIR	Internal Motion Sensor
B1	BACnet™/IP
B2	BACnet™ MS/TP
K	KNX®
L	LON®
M	MODBUS® RTU RS485
AO	Airmaster Airlinq® Online