AIRMASTER®
ventilation in balance

Nomenclature / Plate System Airmaster Products AM 1000

AM 1000 HH TT-CP,PHS,ICO

Series:
AM

Type:
1000

Version:

1. Character:
HH – Horizontal Exhaust/Horizontal Supply
HV – Horizontal Exhaust/Vertical Supply
VV –Vertical Exhaust/Vertical Supply
S1S2 – Side Exhaust/Side Supply

2. Character
TT – Inlet/Extract Top
BB – Inlet/Extract Bottom
TB – Inlet Top/Extract Bottom
DIT – Ducted Inlet/Extract Top
TDE - Inlet Top/ Ducted Extract
BDE - Inlet Bottom/ Ducted Extract
DIDE- Ducted Inlet/Ducted Extract

Options:

AA	Adaptive Airflow™, automatically adjustable
ADA	Adaptive Airflow™, manually adjustable
ANC	Active Noise Control
BP	Bypass (standard)
CH	Comfort Heater
CP	Condensate Pump
CR	Capacitive Return for ED and SD
ED	Motor-driven Exhaust Air Damper (standard)
EM	Energy Meter
ePM_{10} 50%	Supply air filter ePM_{10} 50%
ePM_1 55%	Supply air filter ePM_1 55%
ePM_1 80%	Supply air filter ePM_1 80% (special part)
PHS	PreHeating Surface
SD	Motor-driven Supply Air Damper (standard)
WCH	Water Comfort Heater
CO	External CO_2 Sensor
HY	External Hygrostat
ICO	Internal CO_2 Sensor
ICT	Internal CO_2-/TVOC Sensor
IPIR	Internal Motion Sensor
IT	Internal TVOC Sensor
PIR	External Motion Sensor
B1	BACnet™/IP
B2	BACnet™ MS/TP
K	KNX®
L	LON®
M	MODBUS® RTU RS485
AO	Airmaster Airlinq® Online